



STATE OF ISRAEL



to certify that
hereto is a true
the documents as
deposited with
application
of which are
the first page

זאת לתעודה כי
רצופים בזה העתקים
נכונים של המסמכים
שהופקדו לכתחילה
עם הבקשה לפטנט
לפי הפרטים הרשומים
בעמוד הראשון של
הנספח.

01-09-1999

This _____ היום

מ/סרי
זמונה על הבוחנים

רשם הפטנטים

לשימוש הלשכה
For Office Use

מספר: Number	126007
תאריך: Date	31-08-1998
הוקדם/נדחה Ante/Post-dates	

חוק הפטנטים, התשכ"ז -- 1967
PATENTS LAW, 5727-1967

בקשה לפטנט
Application for Patent

C:31395

אני, (שם המבקש, מעט -- ולגבי גוף מאוגד -- מקום התאגדותו)
I (Name and address of applicant, and, in case of body corporate-place of incorporation)

HI-G-TEK LTD.
16 Hacharoshet Street
Or-Yehuda 60375

היי.ג. טק בע"מ
רחוב החרושת 16
אור יהודה 60375

(An Israeli Company)

(חברה ישראלית)

ששמה הוא By Law
Owner, by virtue of

בעל אמצאה מכח הדין
of an invention, the title of which is:

רשת חוטים אלקטרונית
(בעברית)
(Hebrew)

ELECTRONIC FILAMENT NETTING

(באנגלית)
(English)

hereby apply for a patent to be granted to me in respect thereof

מבקש בזאת כי ינתן לי עליה פטנט

* בקשה חלוקה - Application for Division		* בקשת פטנט מוסף - Application for Patent of Addition		* דרישה דין קדימה Priority Claim		
מבקשת פטנט from Application	* לבקשה/לפטנט to Patent/Appl.	מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country		
No. _____ מס. dated _____ מיום	No. _____ מס. dated _____ מיום					
* יפוי כת: כללי/מיוחד - רצוף בזה / עוד יוגש P.O.A.: general / individual - attached / to be filed later - הוגש בענין _____ המקום למסירת הודעות ומסמכים בישראל Address for Service in Israel Sanford T. Colb & Co. P.O.B. 2273 Rehovot 76122						
חתימת המבקש Signature of Applicant		היום 31 בחודש August שנת 1998 This of the year				
For the Applicant, Sanford T. Colb & Co. C:31395		לשימוש הלשכה For Office Use				

טופס זה, כשהוא מוטבע בחותם לשכת הפטנטים ומושלם בספר ובתאריך ההגשה, הינו אישור להגשת הבקשה שפרטיה רשומים לעיל.
This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application, the particulars of which are set out above.

* מחק את המיותר Delete whatever is inapplicable

רשת חוטים אלקטרונית

ELECTRONIC FILAMENT NETTING

HI-G-TEK LTD.
C: 31395

היי.ג. טק בע"מ

ELECTRONIC FILAMENT NETTING

FIELD OF THE INVENTION

The present invention relates generally to security nets and meshes and particularly to an electronic security net or mesh for placing around cargo and the like.

BACKGROUND OF THE INVENTION

It is essential to protect cargo, freighted by ship, air, rails or truck, from tampering and theft. Valuable cargo passing through freight terminals is prone to attempts by unscrupulous persons to open the cargo and pilfer the contents. Thus there is a well established need for simple and efficient apparatus for monitoring cargo and alerting of attempts to tamper with or steal the contents.

SUMMARY OF THE INVENTION

The present invention seeks to provide simple and efficient apparatus for monitoring cargo and alerting of attempts to tamper with or steal the contents. The present invention provides an electronic filament netting which includes electrical monitoring apparatus. The netting is draped over the object to be protected and any attempt to tamper with the netting causes a change in an initial electrical parameter, which change is communicated to the electronic monitoring apparatus which can then actuate an alarm.

There is thus provided in accordance with a preferred embodiment of the present invention an electronic filament netting including a warp of a first plurality of wires woven together with a weft of a second plurality of wires, wherein a random number of the warp and the weft wires are electrically connected to electronic monitoring apparatus so as to create a random electrical connection which defines an initial electrical parameter, wherein a change in the initial electrical parameter is communicated to the electronic monitoring apparatus.

In accordance with a preferred embodiment of the present invention the warp and the weft wires are electrically connected in a random manner to a bus in electrical communication with the electronic monitoring apparatus.

Further in accordance with a preferred embodiment of the present invention the warp and the weft wires are embedded in a material suitable for draping over an object to be protected.

Still further in accordance with a preferred embodiment of the present invention the warp and the weft wires are pre-manufactured in random electrical connection with the bus.

5 Additionally in accordance with a preferred embodiment of the present invention the bus is attached to an object to be protected.

In accordance with a preferred embodiment of the present invention at a junction between one of the warp wires and one of the weft wires, either one of the warp wires or weft wires is looped around the other wire.

10 Further in accordance with a preferred embodiment of the present invention the warp and the weft wires include electrically resistive elements.

Still further in accordance with a preferred embodiment of the present invention at least one of the warp and the weft wires includes a multiplicity of resistive wires, wherein only a random number of the resistive wires are electrically connected to an electrical terminal of the electronic monitoring apparatus.

15 Additionally in accordance with a preferred embodiment of the present invention the electronic monitoring apparatus includes a multiplexer to which are electrically connected the warp and the weft wires.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

Figs. 1 and 2 are simplified block diagrams of an electronic filament netting constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 3 is a simplified illustration of warp and weft wires looped around each other in the electronic filament netting of Fig. 1;

25 Figs. 4 and 5 are simplified illustrations of the electronic filament netting of Fig. 1 placed around airplane cargo; and

Fig. 6 is a simplified illustration of the electronic filament netting of Fig. 1 placed around truck cargo.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

30 Reference is now made to Figs. 1 and 2 which illustrate in block diagram form an electronic filament netting 10. Netting 10 preferably includes a warp of a first plurality of wires 12 woven together with a weft of a second plurality of wires 14, wherein a random

number of warp and weft wires 12 and 14 are electrically connected to electronic monitoring apparatus 16.

Preferably the random connection is accomplished by electrically connecting the warp and weft wires 12 and 14 in a random manner to a bus 18 in electrical communication with electronic monitoring apparatus 16. Bus 18 is preferably simply an electrically conductive wire, although other constructions of busses may be employed as well.

Warp and weft wires 12 and 14 may be draped as is over an object to be protected, or alternatively, may be embedded in a material 20, such as a cloth or tarpaulin, suitable for draping over the object to be protected. Warp and weft wires 12 and 14 may be pre-manufactured in random electrical connection with bus 18, in which case bus 18 is preferably embedded in material 20 as well. Alternatively, bus 18 itself is attached to the object to be protected. For example, a cargo palette may be manufactured or reworked to have bus 18 embedded therein. After placing netting 10 over the object to be protected, the ends of warp and weft wires 12 and 14 may then be randomly attached to bus 18. In any case, the random electrical connection defines an initial electrical parameter, such as resistance, capacitance or inductance, for example, and a change in the initial electrical parameter is communicated to electronic monitoring apparatus 16 for monitoring and alerting of any attempt of tampering or theft.

Electronic monitoring apparatus 16 preferably includes, *inter alia*, a multiplexer 22 (ends of the wires being preferably connected to terminals of multiplexer 22), which operates in conjunction with an analog-to-digital converter 24. Preferably one multiplexer is provided for the warp and another for the weft. Electronic monitoring apparatus 16 polls the wires via multiplexers 22 and checks if there has been any change in the initial electrical parameter. Any change detected actuates alarm apparatus to alert of possible tampering. Data relating to the electrical parameter may be sent via the A-D converters 24 as a digital value to a remote monitoring station, such as a station 26 shown in Fig. 5, which is in either wired or wireless communication with electronic monitoring apparatus 16. Suitable controllers may be provided for controlling any portion of electronic monitoring apparatus 16.

In accordance with a preferred embodiment of the present invention, in order to enhance security, electronic monitoring apparatus 16 communicates with monitoring station 26 in an encrypted manner. For example, well known encryption algorithms, such as RC-5, DES or DVB, may be employed. To provide an even greater level of trust, mutual zero-knowledge interaction authentication sessions between electronic monitoring apparatus 16 and monitoring

station 26 may be held, such as the so-called Fiat-Shamir authentication methods taught in US Patent 4,748,668 to Shamir and Fiat, the disclosure of which is incorporated herein by reference.

Referring now to Fig. 3, it is seen that preferably that at a junction between one or more of warp wires 12 and weft wires 14, either one of the wires is looped around the other wire. This arrangement ensures that the wires cannot be lifted away from the object to be protected without changing the electrical parameter and thus ensures that the alarm apparatus will be alerted. The skilled artisan will appreciate that warp wires 12 and weft wires 14 may be arranged in other manners to achieve this goal.

The circuitry comprising wires 12 and 14, electronic monitoring apparatus 16 and bus 18, is preferably constructed in accordance with the teachings of U.S. Patent Application No. 08/815,389, the disclosure of which is incorporated herein by reference. As such, warp and weft wires 12 and 14 may be electrically resistive elements. Warp and weft wires 12 and 14 may include a multiplicity of resistive wires, wherein only a random number of the resistive wires are electrically connected to an electrical terminal of electronic monitoring apparatus 16. As described in U.S. Patent Application No. 08/815,389, the wires 12 and 14 would in this case be preferably constructed of a high resistivity material such as nickel chrome. Each wire is preferably insulated from each other and from the external world. The random connection of the wires to electronic monitoring apparatus 16 results in a statistically random electrical resistance, which resistance cannot be measured from outside netting 10. Alternatively, warp and weft wires 12 and 14 may be electrically inductive or capacitive elements. As another alternative, warp and weft wires 12 and 14 may be frangible elements which when broken alert of a change in the initial electrical parameter.

Referring to Figs. 4, 5 and 6, it is seen that electronic filament netting 10 may be placed around airplane cargo 28 (Figs. 1 and 2) and truck cargo 30 (Fig. 6).

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of the features described hereinabove as well as modifications and variations thereof which would occur to a person of skill in the art upon reading the foregoing description and which are not in the prior art.

CLAIMS

What is claimed is:

1. An electronic filament netting comprising:
a warp of a first plurality of wires woven together with a weft of a second
5 plurality of wires, wherein a random number of said warp and said weft wires are electrically
connected to electronic monitoring apparatus so as to create a random electrical connection
which defines an initial electrical parameter, wherein a change in said initial electrical parameter
is communicated to said electronic monitoring apparatus.
2. The electronic filament netting according to claim 1 and wherein said warp and
10 said weft wires are electrically connected in a random manner to a bus in electrical
communication with said electronic monitoring apparatus.
3. The electronic filament netting according to claim 1 or claim 2 and wherein said
warp and said weft wires are embedded in a material suitable for draping over an object to be
protected.
- 15 4. The electronic filament netting according to claim 2 and wherein said warp and
said weft wires are pre-manufactured in random electrical connection with said bus.
5. The electronic filament netting according to claim 2 and wherein said bus is
attached to an object to be protected.
6. The netting according to claim 1 and wherein at a junction between one of said
20 warp wires and one of said weft wires, said one of said warp wires is looped around said one
of said weft wires.
7. The netting according to claim 1 and wherein at a junction between one of said
warp wires and one of said weft wires, said one of said weft wires is looped around said one of
said warp wires.
- 25 8. The netting according to claim 1 and wherein said warp and said weft wires
comprise electrically resistive elements.
9. The netting according to claim 1 and wherein said warp and said weft wires
comprise electrically capacitive elements.
10. The netting according to claim 1 and wherein said warp and said weft wires
30 comprise electrically inductive elements.
11. The netting according to claim 1 and wherein at least one of said warp and said
weft wires comprises a multiplicity of resistive wires, wherein only a random number of said

resistive wires are electrically connected to an electrical terminal of said electronic monitoring apparatus.

12. The netting according to claim 1 and wherein said electronic monitoring apparatus comprises a multiplexer to which are electrically connected said warp and said weft wires.

13. The netting according to claim 1 and comprising a monitoring station in communication with said electronic monitoring apparatus.

14. The netting according to claim 13 and wherein said monitoring station is in encrypted communication with said electronic monitoring apparatus.

15. The netting according to claim 14 and wherein said encrypted communication comprises a mutual zero-knowledge interaction authentication session.

16. The netting according to any of the preceding claims and substantially as described hereinabove.

17. The netting according to any of the preceding claims and substantially as shown in any of the drawings.

For the Applicant,

Sanford T. Colb & Co.
Advocates & Patent Attorneys
C:31395

FIG. 1




FIG. 2





FIG. 3







FIG. 6



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.